


SERIES 402 STOREFRONT FRAMING



Shear Block • Screw Spline • Can Receptor

This economical 2" X 4-1/2" flush glaze system is available in both shear block and screw spline fabrication methods. Series 402 Storefront can accommodate all standard 1 3/4" entrances as well as WV410 vents. Vertical mullions will accept steel reinforcement to enhance structural performance.



| | |
|---|--|
| <p>STRUCTURAL LOAD (ASTM E330)</p> <p>→ VISIT EFCOCORP.COM</p> | <p>WATER RESISTANCE (ASTM E547 & E331)</p> <p>12 PSF</p> |
| <p>AIR INFILTRATION (ASTM E283)</p> <p><0.06 CFM/FT²</p> | <p>CRF (AAMA 1503)</p> <p>N/A</p> |
| <p>U-FACTOR* (ANSI/NFRC 100/200)</p> <p>N/A</p> | <p>OITC* (ASTM E90 & E413)</p> <p>SCREW SPLINE: 26 - 29</p> |
| <p>STC* (ASTM E90 & E413)</p> <p>SCREW SPLINE: 30-34</p> | |

STANDARD FEATURES

- Open back and shear block door frames with transom bars and bulb type weather stripping
- Accommodates up to 1-1/8" glazing
- Uniform glazing gasket is used for exterior and interior
- The optional Roto-Vent ventilator
- 2-way corner mullions (90° and 135°)
- 3-way corner mullions (T-mullions)
- 0° - 15° and 15° - 30° variable mullions
- Various height intermediate horizontals and sills
- Accessory line of perimeter anchors, pocket fillers, door adaptors, etc.
- Anodized or painted finished available

* Performance dependent on glass selection. Please contact your EFCO sales rep for project specific performance.